

SH
SERIES

Normal Pressure Spray Type Hank Dyeing Machine
(Double Layer)

绞纱染色机

SH系列 常温双层绞纱染色机广泛应用于天然纤维纱线（棉，麻，丝，羊毛等），合成纤维纱线（涤纶，锦纶，腈纶等），混纺纤维纱线（天然纤维和合成纤维混纺而成）。特别适用于染光丝、真丝、人造丝、绢丝、单股细纱、丝光棉及其混纺等绞纱。双层绞纱染色机提高产量和降低浴比的的同时实现了垂直空间利用最大化。

SH Series normal temperature double layer hank yarn dyeing machine is widely used in dyeing natural fiber yarn(cotton, linen, silk, wool, etc.), synthetic fiber yarn(polyester, nylon, acrylic, etc.) and blended fiber yarn. It is particularly suitable for dyeing spun silk, pure silk, artificial silk, single-strand fine yarn, mercerized cotton yarn and their blends. Double-layer hank dyeing machine maximizes vertical space utilization while improving productivity and reducing liquor ratio.



技术规格 SPECIFICATIONS:

型号 Model	载量 Capacity (KG)	喷管数 Number of spray pipe	主功率 Main Power (KW)	外型尺寸 Dimensions		
				L(mm)	W(mm)	H(mm)
SH-21T-150	300	21	11	4000	3150	2850
SH-30T-150	450	30	15	5700	3150	2850
SH-42T-150	600	42	18.5	7500	3150	2850
SH-50T-150	750	50	22	9000	3150	2900
SH-62T-150	1000	62	30	10080	3150	2900
SH-80T-150	1200	80	37	13300	3200	3120
SH-100T-150	1500	100	45	16500	3200	3120
SH-120T-150	1800	120	55	19500	3200	3120
SH-200T-150	3000	200	90	16500	7000	3120
SH-240T-150	3600	240	110	19500	7000	3120

敝司保留技术最后之修改权利而不再另行通知。
We reserve our rights to change the specification without prior notice.

